

ProFLEX PU

Product Information

velflex
Heat Transfer Specialists

High Quality Heat Transfer Flex Film for CAD Cutting / Plotting



ProFLEX PU vinyl is a thermo-weldable film developed specifically for the cutting of lettering and small, intricate logos for non-siliconed textiles. Cut to shape using a plotter, ProFLEX PU is easily applied to textiles with a commercial heat press. Its adhesive carrier allows for extremely easy weeding of small logos and lettering.

Available in a wide range of colours and washable up to 80°C, ProFLEX is the smart choice for all kinds of small, one-colour designs.

Technical Information:

- Material for CAD cutting/plotting
- Washable up to 80°C
- Transfers to cloth: 8 - 12 seconds / 140°C - 160°C / 1.5 - 2 bar
Except Reflective: 8 - 15 seconds / 160°C - 165°C / 1.5 - 2 bar
- OKO-TEX STD 100 certified

Packaging:

- Rolls of 25 metres - width: 50cm
- By the metre - width: 50cm

Composition:

- *Base:* film thermocollant
- *Adhesive:* Synthetic resin
- *Total weight:* approx 180 g/sqm without carrier
- *Thickness:* 0.50mm (0.55mm including carrier)

Application to material:

- Cotton
- Polyester
- Polyester/cotton
- Lycra



Also Available in REFLECTIVE

