



DIGITAL INVITE LIGHT NYLON

Our best selling Digital vinyl just got even more impressive! Introducing Digital Invite Light Nylon.

With specially formulated glues rated for application onto nylon and treated fabrics, this vinyl shares the same easy to use features as our regular Digital Invite Light but allows for a wider range of applications. Press onto nylon and treated fabrics with confidence. This vinyls opens up opportunities to decorate garments that may otherwise be too difficult to press onto. Broaden your offering with Invite Light Nylon!

RECOMMENDED FABRICS

- Cotton/Polyester Blends
- Nylon
- Treated Fabric

Please note: Always check fabric makeup and test press when possible.

TECHNICAL INFORMATION

Thickness: 70 Microns

Finish: Matte

Carrier: Medium/High Tack

Rating: OEKO- TEK Standard 100 Certified

PRINT INSTRUCTIONS

Printer: Mild Solvent / Eco Solvent

Mode: Print & Cut

Recommended Profile: Contact us for info

HEATERS

Pre: 30-35°C (environment dependant)

Print: 30-35°C (environment dependant)

Post: 30-40°C (environment dependant)

FOR USE WITH

- Stahls High Tack Application Tape
- Commercial Heat Press

WASHING INSTRUCTIONS

- Avoid in the first 24 hours
- No higher than 40°C
- Do not dry clean or tumble dry
- Hang dry inside-out
- Avoid over exposure to direct sunlight

CUTTING NOTES

Blade: Standard Cutting Blade (45°)

Pressure: From 60g (New blade)

Recommended cut size: 5mm Text (for fast weeding)

Please note: Always test cut prior to any production. Remember cutter settings will need to be adjusted between products and as your blade ages.


plotterfilms
thermotransfer materials
by So.L.Ter



APPLICATION INSTRUCTIONS

Temperature: 150°C

Time: 12 seconds

Pressure: Medium / 50-60psi / 4bar / #5-6 on Hotronix

Peel: Hot (Immediate)

☎ 1300 765 414 ✉ sales@velflex.com.au

WWW.VELFLEX.COM.AU