



DIGITAL SUPER LIGHT

Designed for superior stretch, this new printable vinyl is rated for high stretch fabrics or lightweight cotton tees. Digital Super Light moves with the wearer without cracking or buckling - perfect for sportswear/gym wear or other high performance gear. This vinyl is the thinnest in the Velflex range - almost HALF the thickness of regular print vinyls. This allows it to feel like part of the garment and truly live up to its name.

Previous stretch vinyls have been difficult to work with due to their inability to release from the carriers or being too sensitive to heat. This vinyl blends the printability of our everyday vinyl with the feel and finished look of a specialty product. This product responds best when left to dry (best results when left overnight) between printing and cutting.

RECOMMENDED FABRICS

- Cotton/Polyester Blends
- Lycra
- Spandex

Please note: Always check fabric makeup and test press when possible.

TECHNICAL INFORMATION

Thickness: 55 Microns

Finish: Matte

Carrier: Medium/High Tack

Rating: OEKO- TEK Standard 100 Certified

PRINT INSTRUCTIONS

Printer: Mild Solvent / Eco Solvent

Mode: Print & Cut

Recommended Profile: Contact us for info

HEATERS

Pre: 30-35°C (environment dependant)

Print: 30-35°C (environment dependant)

Post: 30-40°C (environment dependant)

FOR USE WITH

- Stahls High Tack Application Tape
- Commercial Heat Press

WASHING INSTRUCTIONS

- Avoid in the first 24 hours
- No higher than 40°C
- Do not dry clean or tumble dry
- Hang dry inside-out
- Avoid over exposure to direct sunlight

CUTTING NOTES

Blade: Standard Cutting Blade (45°)

Pressure: From 50g (New blade)

Recommended cut size: 5mm Text (for fast weeding)

Please note: Always test cut prior to any production. Remember cutter settings will need to be adjusted between products and as your blade ages.


plotterfilms
thermotransfer materials
by So.L.Ter



APPLICATION INSTRUCTIONS

Temperature: 150°C

Time: 12 seconds

Pressure: Medium / 50-60psi / 4bar / #5-6 on Hotronix

Peel: Hot (Immediate)

☎ 1300 765 414 ✉ sales@velflex.com.au

WWW.VELFLEX.COM.AU