



FLEX MIRROR

As the name suggests, this mirror vinyl is a great way to add a chrome/mirror finish to your designs. This vinyl offers a rich and shiny finish that stands out from the crowd and demands to be noticed.

RECOMMENDED FABRICS

- Cotton
- Polyester
- Cotton/Polyester Blends

Please note: Always check fabric makeup and test press when possible.

TECHNICAL INFORMATION

Thickness: 90 Microns

Finish: Mirror

Carrier: Medium/High Tack

Rating: OEKO- TEK Standard 100 Certified

WASHING INSTRUCTIONS

- Avoid washing in the first 24 hours
- No higher than 40°C
- Do not dry clean or tumble dry
- Hang dry inside-out
- Avoid over exposure to direct sunlight

FOR USE WITH

- Commercial Heat Press
- Vinyl Cutter
- Weeding Tool

CUTTING NOTES

Blade: Standard Cutting Blade (45°)

Pressure: From 60g (New blade)

Recommended cut size: 5mm Text (for fast weeding)

Please note: Always test cut prior to any production. Remember cutter settings will need to be adjusted between products and as your blade ages.


plotterfilms
thermotransfer materials
by So.L.Ter



APPLICATION INSTRUCTIONS

Temperature: 150°C

Time: 12 seconds

Pressure: Medium / 50-60psi / 4bar / #5-6 on Hotronix

Peel: Warm

☎ 1300 765 414 ✉ sales@velflex.com.au

WWW.VELFLEX.COM.AU