



# FLEX NYLON

Featuring a special glue, Flex Nylon is specifically designed for application onto typically 'difficult to press' fabrics. Decorate nylon jackets, outdoor and water resistant fabrics, technical apparel, umbrellas, gazebos - the list goes on! This vinyl opens the door for 'out of the box' decoration.

## RECOMMENDED FABRICS

- Cotton
- Polyester
- Cotton/Polyester Blends

Please note: Always check fabric makeup and test press when possible.

## TECHNICAL INFORMATION

**Thickness:** 90 Microns

**Finish:** Matte

**Carrier:** Medium/High Tack

**Rating:** OEKO- TEK Standard 100 Certified

## WASHING INSTRUCTIONS

- Avoid washing in the first 24 hours
- No higher than 40°C
- Do not dry clean or tumble dry
- Hang dry inside-out
- Avoid over exposure to direct sunlight

## FOR USE WITH

- Commercial Heat Press
- Vinyl Cutter
- Weeding Tool

## CUTTING NOTES



**Blade:** Standard Cutting Blade (45°)

**Pressure:** From 60g (New blade)

**Recommended cut size:** 5mm Text (for fast weeding)

**Please note:** Always test cut prior to any production.

Remember cutter settings will need to be adjusted between products and as your blade ages.

  
**plotterfilms**  
thermotransfer materials  
by So.L.Ter 



## APPLICATION INSTRUCTIONS

**Temperature:** 150°C

**Time:** 12 seconds

**Pressure:** Medium / 50-60psi / 4bar / #5-6 on Hotronix

**Peel:** Hot (Immediate)

 1300 765 414  [sales@velflex.com.au](mailto:sales@velflex.com.au)

[WWW.VELFLEX.COM.AU](http://WWW.VELFLEX.COM.AU)