



FLEX SOFT SHELL

Pressing onto soft shell or technical fabrics? Flex Soft Shell is your answer! With an anti-migration layer and glues specifically designed to adhere to soft shell fabric, this low temperature, quick press vinyl is perfect for those 'difficult to press' garments/fabrics.

RECOMMENDED FABRICS

- Soft Shell Fabric
- Nylon/Treated Fabric (some, not all)
- Cotton/Polyester Blends
- Sublimated Fabric

Please note: Always check fabric makeup and test press when possible.

TECHNICAL INFORMATION

Thickness: 160 Microns

Finish: Matte/Matte Metallic

Carrier: Medium/High Tack

Rating: OEKO- TEK Standard 100 Certified

WASHING INSTRUCTIONS

- Avoid washing in the first 24 hours
- No higher than 40°C
- Do not dry clean or tumble dry
- Hang dry inside-out
- Avoid over exposure to direct sunlight

FOR USE WITH

- Commercial Heat Press
- Vinyl Cutter
- Weeding Tool

CUTTING NOTES

Blade: Standard Cutting Blade (45°)

Pressure: From 80g (New blade)

Recommended cut size: 20mm Text (for fast weeding)

Please note: Always test cut prior to any production.

Remember cutter settings will need to be adjusted between products and as your blade ages.


thermotransfer materials
by So.L.Ter



APPLICATION INSTRUCTIONS

Temperature: 140°C

Time: 8 seconds

Pressure: Medium / 50-60psi / 4bar /
#5-6 on Hotronix

Peel: Warm